

DATASHEET

DMF3X5R5J204M3DTA0

5.5V, 200mF, 105mΩ, -40°C to +70°C

v1.4, Aug 2023



Electrical Specifications

Table 1: Absolute Maximum Ratings

| Parameter | Name | Conditions | Min | Typical | Max | Units |
|------------------|------------|------------|-----|---------|-----|-------|
| Terminal Voltage | V_{peak} | | | | 5.5 | V |
| Temperature | T_{max} | | -40 | | +70 | °C |


Table 2: Electrical Characteristics

| Parameter | Name | Conditions | Min | Typical | Max | Units |
|---------------------------|-------|----------------------|-----|---------|-----|-------|
| Terminal Voltage | V_n | | 0 | | 5.5 | V |
| Capacitance | C | DC, 23°C | 160 | 200 | 240 | mF |
| ESR | ESR | AC, 1kHz | | 105 | 125 | mΩ |
| Leakage Current | I_L | 5.5V, 23°C 120hrs | | | 2 | μA |
| Peak Current ¹ | I_P | 23°C | | | 15 | A |

¹Non-repetitive current, single pulse to discharge fully charged supercapacitor.


Table 3: Mechanical specification

| | Length (mm) | Width (mm) | Thickness "T" (mm) | Weight (gm) |
|---|-------------|------------|--------------------|-------------|
| DMF3X5R5J204M3DTA0 | 21 ± 0.5mm | 14 ± 0.5 | 1.9 (max. 2.2) | 0.6 |
| DMF3X5R5J204M3DTA1 (with adhesive tape on underside) | 21 ± 0.5mm | 14 ± 0.5 | 2.1 (max. 2.4) | 0.6 |




Mechanical drawing for DMF3X5R5J204M3DTA0

Landing Pad Dimensions



Part Numbering



① Series

| Code | |
|------------|----------------------|
| DMF | High Peak Power Type |

② External Dimensions (L x W x T)

| Code | L (mm) | W (mm) | T (mm) |
|-----------|----------|----------|---------------|
| 3X | 21.0±0.5 | 14.0±0.5 | 1.9 (max 2.2) |

③ Rated Voltage

| Code | Rated Voltage |
|------------|---------------|
| 5R5 | DC 5.5V |

④ ESR

| Code | ESR @ 1kHz |
|----------|------------|
| J | 105mΩ |

⑤ Nominal Capacitance

First two are significant digits and the third expresses the number of zeroes which follow the two numbers

| Code | Nominal Capacitance |
|------------|-------------------------------|
| 204 | 20x10 ⁴ μF = 200mF |

⑥ Capacitance Tolerance

| Code | Tolerance |
|----------|-----------|
| M | ±20% |

⑦ External Terminal

| Code | Terminal Specification |
|-----------|---------------------------|
| 3D | 3 Terminals (+/-/Balance) |

⑧ Packaging


| Code | Package Specification |
|----------|-----------------------|
| T | Tray type, 50pcs/Tray |

⑨ Inhouse Specification Code

Expressed by two-digit alphanumerics

Printing

Capacitance Series Code + LW Size Code



Batch ID

Manufacturer (CAP-XX)

Negative Terminal

Balance Terminal

Positive Terminal

Rated Voltage

Batch ID

| | | | | |
|--|--|--|--|--|
| | | | | |
|--|--|--|--|--|

①

②

③

① Year

| Code | Year |
|------|------|
| 9 | 2019 |
| A | 2020 |
| B | 2021 |
| C | 2022 |
| D | 2023 |
| : | : |
| Y | 2044 |
| Z | 2045 |

② Month

| Code | Month |
|------|-----------|
| F | January |
| G | February |
| H | March |
| J | April |
| K | May |
| L | June |
| M | July |
| N | August |
| P | September |
| Q | October |
| R | November |
| S | December |

③ 3-digit Unique ID

This 3 digit number is used to uniquely identify the batch within the month.

Definition of Terms

In its simplest form, the Equivalent Series Resistance (ESR) of a capacitor is the real part of the complex impedance. In the time domain, it can be found by applying a step discharge current to a charged cell as in Fig. 1. In this figure, the supercapacitor is pre-charged and then discharged with a current pulse, $I = 1.1\text{A}$ for duration 0.01 sec .




Fig 1: Effective capacitance, instantaneous capacitance and ESR for DMF3X5R5J204M3DTA0

The ESR is found by dividing the instantaneous voltage step (ΔV) by I . In this example $= (5.49\text{V} - 5.375\text{V})/1.16\text{A} = 99\text{m}\Omega$.

The instantaneous capacitance (C_i) can be found by taking the inverse of the derivative of the voltage, and multiplying it by I .

The effective capacitance for a pulse of duration Δt_n , $C_e(\Delta t_n)$ is found by dividing the total charge removed from the capacitor (ΔQ_n) by the voltage lost by the capacitor (ΔV_n). For constant current $C_e(\Delta t_n) = I \times \Delta t_n / \Delta V_n$. C_e increases as the pulse width increases and tends to the DC capacitance value as the pulse width becomes very long ($\sim 10\text{ secs}$). After 2msecs, Fig 1 shows the voltage drop $V_{2\text{ms}} = (5.375\text{ V} - 5.334\text{V}) = 41\text{mV}$. Therefore $C_e(2\text{ms}) = 1.16\text{A} \times 2\text{ms} / 41\text{mV} = 56.6\text{mF}$. After 10ms, the voltage drop $= 5.375\text{ V} - 5.265\text{V} = 110\text{mV}$. Therefore $C_e(10\text{ms}) = 1.16\text{ A} \times 10\text{ms} / 110\text{mV} = 105\text{mF}$. The DC capacitance of DMF3X5R5J204M3DTA0 = 0.2 F. Note that ΔV , or $I \cdot R$ drop, is not included because very little charge is removed from the capacitor during this time. C_e shows the time response of the capacitor and it is useful for predicting circuit behaviour in pulsed applications.

Measurement of DC Capacitance




Fig 2: Measurement of DC Capacitance for a DMF3X5R5J204M3DTA0

Fig 2 shows the measurement of DC capacitance by drawing a constant 100mA current from a fully charged supercapacitor and measuring the time taken to discharge from 80% to 40% of V_{rated} . In this case, $C = 0.096A \times 4.73s / (4.4-2.2)V = 206mF$, which is within the 200mF +/- 20% tolerance for a DMF3X5R5J204M3DTA0 cell.

Measurement of ESR




Fig 3: Measurement of ESR for a DMF3X5R5J204M3DTA0

Fig 3 shows DC measurement of ESR by applying a step load current to the supercapacitor and measuring the resulting voltage drop. CAP-XX waits for a delay of 50μs after the step current is applied to ensure the voltage and current have settled. In this case the ESR is measured as $95.4mV/1.1A = 86.7m\Omega$.

Effective Capacitance




Fig 4: Effective Capacitance

Fig 4 shows the effective capacitance for the DMF3X5R5J204M3DTA0 @ 23°C. This shows that for a 1msec PW, you will measure 10% of DC capacitance or 20mF. At 10msecs you will measure 43% of the DC capacitance, and at 100msecs you will measure 80% of DC capacitance. Effective is a time domain representation of the supercapacitor's frequency response. If, for example, you were calculating the voltage drop if the supercapacitor was supporting 1A for 10msecs, then you would use the $C_{eff}(10msecs) = 43\%$ of DC capacitance = 86mF, so $V_{drop} = 1A \times ESR + 1A \times \text{duration}/C = 1A \times 105m\Omega + 1A \times 10ms / 86mF = 221mV$.

DC Capacitance variation with temperature




Fig 5: Capacitance change with temperature

Fig 6 shows that DC capacitance is approximately constant with temperature.

ESR variation with temperature




Fig 6: ESR change with temperature

Fig 6 shows that ESR at -40°C is ~1.8 x ESR at room temp, and that ESR at 70°C is ~0.8 x ESR at room temperature.

RMS Current





Fig 7: Temperature rise in DMF3X5R5J204M3DTA0 with RMS current

Continuous current flow into/out of the supercapacitor will cause self-heating, which limits the maximum continuous current the supercapacitor can handle. This is measured by a current square wave with 50% duty cycle, charging the supercapacitor to rated voltage at a constant current, then discharging the supercapacitor to half rated voltage at the same constant current value. For a square wave with 50% duty cycle, the RMS current is the same as the current amplitude. Fig 7 shows the increase in temperature as a function of RMS current. From this, the maximum RMS current in an application can be calculated, for example, if the ambient temperature is 40°C, and the maximum desired temperature for the supercapacitor is 70°C, then the maximum RMS current should be limited to 3.7A, which causes a 30°C temperature increase.

Packaging

DMF3X5R5J204M3DTA0



Storage

CAP-XX recommends storing supercapacitors in their original packaging in an air-conditioned room at < 30°C and < 60% relative humidity. CAP-XX supercapacitors can be stored at any temperature not exceeding their maximum operating temperature but storage at continuous high temperature and humidity is not recommended and will cause premature ageing.

Do not store supercapacitors in the following environments:

- High temperature / high humidity
- Direct sunlight
- In direct contact with water, salt, oil or other chemicals
- In direct contact with corrosive materials, acids, alkalis or toxic gases
- Dusty environment
- In environments subjected to shock and vibration

Cautions before use

CAP-XX supercapacitors are “burned in” during production, and have a defined polarity, as shown by the positive terminal marked on the face of the product. Reversing the polarity of the device will not damage the device but may cause a rise in the ESR and will void the warranty. Please verify the orientation of the supercapacitor in accordance with the product markings before assembly.

CAP-XX supercapacitors are heat-sensitive. Over-heating of the supercapacitor may result in a degradation of performance and useful life.

CAP-XX supercapacitors must only be used within their rated voltage range. Over-voltage may cause swelling and eventually, product failure.

CAP-XX supercapacitors are fully discharged when shipped. Devices should be handled and soldered in a discharged state.

Soldering and Assembling

CAP-XX supercapacitors are designed for direct soldering onto the PCB. Soldering the terminals to the PCB will ensure the highest contact reliability and lowest contact resistance. Do NOT solder directly to the device casing. This will cause permanent internal damage to the supercapacitor.

CAP-XX supercapacitors are NOT SUITABLE for infrared reflow soldering, hot-air reflow soldering, or wave soldering. They should be mounted as a secondary operation, using a manual soldering iron, a hot bar soldering jig, conductive adhesive, ultrasonic welding or laser welding.

CAP-XX recommends the use of a water-soluble flux, or a no-clean (low residue) flux, and low temperature solder compounds.

Please solder under the following conditions:

- Solder Type: Resin flux cored solder wire (Ø1.2mm)
- Solder: Lead-free solder: Sn-3Ag-0.5Cu
- Soldering iron temperature at 350°C±10°C
- Solder iron wattage: 70W or less
- Soldering time: 3 to 4sec.
- The same terminal should be soldered 3 or less times.

If a hot-air gun is used to reflow the solder during a re-mount or de-mount, care must be taken to prevent excessive heating of the package adjacent to the solder terminals. Allow at least 15 sec between successive soldering attempts for the device to cool down.

Please consult CAP-XX if you wish to wash the device after soldering.
